



ANSI / NEMA / OSHA Safety Signs

- Indoor/outdoor durable up to 30 years
- Conforms to ANSI Z535, NEMA and OSHA standards
- Versatile attachments
- Custom sizes available

Description

Durable indoor/outdoor signs communicate your important information, identify potential hazards, and help prevent accidents season after season.

ANSI Compliant Message and Colors

ANSI Z535 safety symbols include DANGER, WARNING, CAUTION, NOTICE, and ATTENTION. Our ANSI/NEMA/OSHA signs adhere to the most up-to-date specifications.

William Frick manufactures safety signs from many materials. Please refer to the table below to select the right material for your job. Our safety experts are available to assist you during the ordering process.

Create Signs Using



| | | | | | | |
|-------------------|---------------------------------------|-----------------------------------|---------------------------|------------------------------------|------------------------------|---------------------------------------|
| Material | Aluminum | Polyethylene | Co-Extruded Poly | Fiberglass | Steel/Porcelain | Lexan® |
| Outdoor Life | 10+ years | 5-10 years | 30 years | 10-15 years | 25 years | 10-15 years |
| Vandal Resistance | No | No | Yes | Yes | Yes | Yes |
| Features | Reflective or non-reflective finishes | Excellent for indoor applications | Permanently engraved text | Embedded graphics. Low maintenance | Excellent outdoor durability | Embedded graphics. Graffiti resistant |
| Thickness | 0.025-0.080 inch | 0.035-0.125 inch | 0.080 inch | 0.90-0.125 inch | 0.044-0.070 inch | 0.90 inch |
| Lead Times | 2 weeks | 2-3 weeks | 2-3 weeks | 2 weeks | 4-8 weeks | 2-3 weeks |

Additional information

| | |
|--------------|----------------------------------------------------------------------------------------------------|
| Model Number | WFS-ES-0016 ANSI / NEMA / OSHA Safety Signs |
| Applications | Informational Placards, Construction, Harsh Environments, Outdoor Use, Utility Labeling, Warehouse |
| Shelf Life | Completely Stable, Stored at 70F and 50% Relative Humidity |