

# Emergency Hard Hat Labels



- Quickly identify worker health information
- Self laminating flap protects written information from dirt and moisture
- Abrasion resistant and dielectric
- Custom designs and sizes available
- Sold in Packs of 25

## Description

When minutes matter, hard hat labels indicating the wearer's name and vital stats can help save a life! Get the appropriate medical response faster when an accident or injury occurs. Comfortable hard hat labels provide a wrinkle-free, printable surface for vital information to be stored inside hard hats and safety helmets. A special laminating flap protects the wearer's information from contact with dirt and moisture.

## Additional information



|                                 |                                                                                                                                                            |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                          | 0.125 lbs                                                                                                                                                  |
| Dimensions                      | 15 × 11 × 0.25 in                                                                                                                                          |
| Model Number                    | WFS-ES-0029 Hard Hat Emergency Labels                                                                                                                      |
| Applications                    | Construction, Safety & Compliance                                                                                                                          |
| Material                        | Vinyl                                                                                                                                                      |
| Size                            | 6.8"x1.4"                                                                                                                                                  |
| Overall Thickness               | .008 mil ± 10%                                                                                                                                             |
| Expected Outdoor Life           | 3 – 5 Years                                                                                                                                                |
| Temperature Service Range       | -40°F to 255°F                                                                                                                                             |
| Minimum Application Temperature | 50° F                                                                                                                                                      |
| Water Resistance                | Excellent                                                                                                                                                  |
| Oil Resistance                  | Good                                                                                                                                                       |
| Solvents Resistance             | Very Good                                                                                                                                                  |
| UV Resistance                   | Very Good                                                                                                                                                  |
| Abrasion Resistance             | Excellent                                                                                                                                                  |
| Adhesive                        | Permanent Acrylic                                                                                                                                          |
| Adhesion                        | Adhesion to HSE Plastics: Good, Adhesion to LSE Plastics: Good, Adhesion to Glass at 72 hr. dwell: Excellent, Adhesion to Steel at 72 hr. dwell: Excellent |
| Shelf Life                      | 2 Years, Stored at 70F and 50% Relative Humidity                                                                                                           |