



RFID Strap Labels

- Up to 35 ft. read range
- Abrasion, UV, water, oil, and solvent-resistant
- Versatile attachments methods include adhesive and magnetic backing

Description



Our RFID Strap Labels are available with dual magnets on each end to temporarily secured and easily relocated, or with dual-split liner to be permanently secured. The convenient strap installation improves RFID read-range. These labels are abrasion, UV, water, oil, and solvent-resistant.

Additional information



Model Number	WF-SM-STRAP RFID Strap Label
Applications	Appliance Labeling, Identification Labeling, Metal Mount, Asset Marking, Asset Tracking, Barcode Labeling, Container Tagging, Serial labels, Warehouse
Material	Laminated Polyester
Temperature Service Range	-40° F to 302° F
Water Resistance	Excellent
Oil Resistance	Excellent
Solvents Resistance	Excellent
UV Resistance	Very Good
Expected Outdoor Life	5 – 7 Years
Shelf Life	2 Years, Stored at 70F and 50% Relative Humidity

RFID Performance

RFID Protocol	EPC Class 1 Gen 2
Tag Type	Passive Read/Write
Frequency Range	840 – 960 MHz (Global)
User Memory	512 bits
EPC Memory	96 bits
IC	Alien® Higgs® 3